



X2 Instruction Manual

Thank you for choosing Kudos.

Please read through these instructions before using your new Kudos X2 loudspeakers.

Connections

To maintain correct phase make sure to connect the “red +” amplifier connection to the corresponding “red +” speaker connection and the “black -” amplifier connection to the corresponding “black -” speaker connection.

Loudspeaker cables can have a significant effect on the overall sound quality. Ask your dealer or seek advice from the manufacturer of your amplifier on suitable cables for your system.

If in any doubt consult your supplying dealer.

Positioning

The X2 loudspeakers come with a stabilising and port optimising plinth fitted and the supplied spikes and lock collars should be used at all times. For optimum Results it is important to screw the spike and collar all the way into the plinth insert and then back out by one turn! Then you can level the speaker to ensure there is no rocking. If you have a wooden or laminate floor your dealer should be able to supply floor protectors to avoid spike damage to your floor.

Your X2 loudspeakers should be easy to site in your listening room. As a general guide, they should be placed a minimum of 2m apart and at least the same distance away from the main listening position. The X2 is ported through the base of the cabinet which reduces the effects of, and allows closer placement to room boundaries. However, in most circumstances, we would recommend the cabinets are placed at least 45cm away from corners. Moving a loudspeaker closer to room boundaries will increase bass response, but may cause colouration and unevenness in the mid-band. All loudspeakers require a “running-in” period and we recommend you do not decide on the final positioning until your ‘speakers have had at least 30 hours of use.

Once you have become more familiar with your new loudspeakers, a degree of experimentation with their placement can bring about significant improvements.

Power Handling

Providing that you do not run your amplifier into “clipping” (sounding distorted and strained), your Kudos loudspeakers should handle the power from most amplifiers in a domestic setting. As a rough guide, we recommend amplifiers with a power rating of between 25 and 150 watts per channel. Remember that you are much more likely to damage your drive units by using an underpowered amplifier clipping, than an overpowered model used wisely!

General Care

Loudspeakers are inherently reliable and require little maintenance. The cabinets are finished in real wood veneers and can be cleaned with a lightly damp lint free cloth or a very soft dust brush. The grilles can be cleaned using a sticky roller (of the type used for removing pet hair from clothes) if necessary. The grilles are held on to the front of the speaker by magnets. However, we recommend that you keep the grilles off for the first few months of use: wood veneers will mature and darken with time and the use of the grille may result in an uneven colour.

Service and Warranty

Loudspeakers rarely require service, but should the need arise, contact your dealer or local distributor. There are no user serviceable parts inside.

We would advise you to retain all packaging material in case you need to ship or transport your loudspeakers in the future.

All X2 loudspeakers are guaranteed against faulty components and defective materials for a period of 12 months from the date of purchase.

Please complete and return the enclosed warranty card with dealer stamp and proof of purchase to activate your extended 5 year guarantee.

“Some restrictions apply, details upon request”

This warranty does NOT cover damage due to accident, negligence or misuse.
Carriage is at the owner’s expense.

The warranty is restricted to the original purchaser and does not effect your statutory rights

Kudos Audio
Harvey Court
Low Willington Ind. Est.
Co Durham
DL15 0UT
0845 4586698

enquiries@kudosaudio.com
www.kudosaudio.com